

# ODYSSEY® Performance Batteries

Rated Operating Temperature -40°F (-40°C) to 140°F (60°C)

All values shown are nominal unless otherwise noted.

12 volt

NEW PART NUMBER (Old Part Number)	PHCA** 5 sec [A]	CCA* [A]	20 HR Rate [Ah]	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]	Terminal	Maximum Torque [in-lb (Nm)]	Drawing (Battery Reference Table)
ODP-AGM75 86† (75/86-705)	1100	708	49	89	9.5 (240)	6.8 (172)†	7.9 (202)	7.4 (187)	43 (20.0)	SAE & Side †	60 (6.8) side only	C
ODP-AGM96R (96R-600)	1100	600	52	90	9.5 (242)	6.9 (175)	6.8 (174)	6.9 (176)	40 (18.0)	SAE	N/A	A
ODP-AGM47 H5 L2 (47-650 (LN2-H5))	1150	650	64	105	9.5 (242)	6.9 (175)	7.4 (189)	7.5 (190)	42 (19.0)	SAE	N/A	A
ODP-AGM25	1200	675	59	110	9.5 (241)	6.9 (175)	8.6 (219)	7.9 (202)	46 (21.0)	SAE	N/A	B
ODP-AGM35 (35-675)	1200	675	59	110	9.5 (241)	6.9 (175)	8.6 (219)	7.9 (202)	46 (21.0)	SAE	N/A	A
ODP-AGM48 H6 L3 (48-720)	1250	720	69	130	10.9 (277)	6.9 (174)	7.4 (189)	7.5 (191)	48 (22.0)	SAE	N/A	A
ODP-AGM24 (24-725)	1300	725	63	155	10.9 (276)	6.8 (172)	8.8 (224)	8.2 (207)	51 (23.0)	SAE	N/A	B
ODP-AGM24F (24F-725)	1300	725	63	155	10.9 (277)	6.8 (172)	8.8 (224)	8.2 (207)	51 (23.0)	SAE	N/A	A
ODP-AGM34 (A) (34-790)	1500	792	61	124	10.8 (276)	6.8 (172)	7.9 (199)	7.4 (187)	47 (21.0)	SAE	N/A	B
ODP-AGM34 78† (A) (ELT-AGM34/78)	1300	710	60	120	10.9 (277)	6.8 (173)†	7.8 (199)	7.2 (182)	47 (21.0)	SAE & Side †	60 (6.8) side only	C
ODP-AGM34R (A) (34R-790)	1500	792	61	124	10.8 (275)	6.8 (172)	7.9 (199)	7.4 (187)	47 (21.0)	SAE	N/A	A
ODP-AGM78† (78-790)	1500	792	61	124	10.8 (275)	6.8 (172)	7.4 (187)	7.4 (187)	47 (21.0)	Side †	60 (6.8)	D
ODP-AGM65 (H) (A) (65-760)	1500	762	64	129	11.8 (301)	7.2 (183)	7.6 (192)	6.8 (172)	50 (23.0)	SAE	N/A	B
ODP-AGM27 (ELT-AGM27)	1500	850	85	182	12.5 (317)	6.8 (172)	8.8 (224)	8.2 (207)	60 (27.0)	SAE	N/A	B
ODP-AGM27F (ELT-AGM27F)	1500	850	85	182	12.5 (317)	6.8 (172)	8.8 (224)	8.2 (207)	60 (27.0)	SAE	N/A	A
ODP-AGM94R H7 L4 (94R-650)	1500	840	80	155	12.4 (315)	6.9 (174)	7.4 (189)	7.5 (191)	55 (25.0)	SAE	N/A	A
ODP-AGM49 H8 L5 (49-950)	1700	950	94	180	13.9 (353)	6.9 (174)	7.4 (189)	7.5 (191)	63 (29.0)	SAE	N/A	A
ODP-AGM31 (H) (A) (31-925S)	1750	925	100	200	13.0 (330)	6.8 (173)	9.6 (243)	8.6 (220)	70 (32.0)	3/8-16" Stud	200 (22.6)	F
ODP-AGM31A (A) (31-925T)	1750	925	100	200	13.0 (330)	6.8 (173)	9.4 (240)	8.6 (220)	70 (32.0)	SAE	N/A	F
ODP-AGM4D (4D-1300)	2400	1300	170	370	20.4 (518)	8.8 (223)	8.6 (218)	8.3 (208)	117 (53.0)	SAE	N/A	I
ODP-AGM8D (NSB-AGM8D)	2700	1450	220	500	20.4 (517)	10.8 (275)	9.5 (242)	8.5 (215)	152 (69.0)	SAE	N/A	I
ODP-AGM8DT (NSB-AGM8DS)	2700	1450	220	500	20.4 (517)	10.8 (275)	9.5 (242)	8.5 (215)	152 (69.0)	Stud	200 (22.6)	I

