














# NorthStar PRO Battery Specifications

NEW PART NUMBER (Old Part Number)	Voltage	PHCA** 5 sec. [A]	CCA* [A]	HCA* [A]	MCA* [A]	20 HR Rate [Ah]	10 HR Rate [Ah]	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Height [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]	Terminal	Maximum Torque [in-lb (Nm)]	Internal Resistance [mΩ]	Terminal Layout
 NSB-AGM8DS	12	2700	1450	2150	1800	220	211	500	20.4 (518)	10.8 (274)	9.5 (241)	8.5 (216)	152 (68.9)	3/8-16" Stud	200 (22.6)	1.7	<a href="#">View</a>	
 NSB-AGM8D	12	2700	1450	2150	1800	220	211	500	20.4 (518)	10.8 (274)	9.5 (241)	8.5 (216)	152 (68.9)	SAE	N/A	1.7	<a href="#">View</a>	
 NSB-AGM65M	12	1750	930	1280	1070	69	64	135	11.76 (299)	7.32 (186)	7.42 (188)	0	54 (24.5)	M	200 (22.6)/100 (11.3) studs only	3.3	<a href="#">View</a>	
 NSB-AGM34M	12	1500	880	1250	1050	65	61	134	10.9 (277)	6.8 (173)	7.8 (198)	7.2 (183)	50.9 (23.1)	M	200 (22.6)/100 (11.3) studs only	3.6	<a href="#">View</a>	
 NSB-AGM31M	12	2150	1150	1545	1370	103	98	220	13 (330)	6.8 (173)	9.9 (251)	8.9 (226)	75.2 (34.1)	M	200 (22.6)/100 (11.3) studs only	2.2	<a href="#">View</a>	
 NSB-AGM31A	12	2150	1150	1545	1370	103	98	220	13 (330)	6.8 (173)	9.7 (246)	8.5 (216)	75.2 (34.1)	SAE	N/A	2.2	<a href="#">View</a>	
 NSB-AGM31	12	2150	1150	1545	1370	103	98	220	13 (330)	6.8 (173)	9.4 (239)	8.5 (216)	75.2 (34.1)	3/8-16" Stud	200 (22.6)	2.2	<a href="#">View</a>	
 NSB-AGM27M	12	1750	930	1290	1080	92	88	195	12.5 (318)	6.8 (173)	8.8 (224)	8.2 (208)	67.9 (30.8)	M	200 (22.6)/100 (11.3) studs only	2.6	<a href="#">View</a>	
 NSB-AGM27F	12	1750	930	1290	1080	92	88	195	12.5 (318)	6.8 (173)	8.8 (224)	8.2 (208)	67.9 (30.8)	SAE	N/A	2.6	<a href="#">View</a>	
 NSB-AGM27	12	1750	930	1290	1080	92	88	195	12.5 (318)	6.8 (173)	8.8 (224)	8.2 (208)	67.9 (30.8)	SAE	N/A	2.6	<a href="#">View</a>	
 NSB-AGM24M	12	1500	840	1200	1000	76	73	160	10.9 (277)	6.8 (173)	8.8 (224)	8.2 (208)	57.1 (25.9)	M	200 (22.6)/100 (11.3) studs only	3	<a href="#">View</a>	
 NSB-AGM24F	12	1500	840	1200	1000	76	73	160	10.9 (277)	6.8 (173)	8.8 (224)	8.2 (208)	57.1 (25.9)	SAE	N/A	3		
 NSB-AGM24	12	1500	840	1200	1000	76	73	160	10.9 (277)	6.8 (173)	8.8 (224)	8.2 (208)	57.1 (25.9)	SAE	N/A	3		