

ODYSSEY® Extreme Batteries

12 volt

PART NUMBER	PHCA 5 sec [A]	MCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODX-AGM24M	1500	1010	76	160	10.9 (276)	6.8 (172)	8.8 (222)	8.1 (206)	57 (26.0)
ODX-AGM34M	1500	1050	68	135	10.9 (276)	6.8 (172)	8.0 (202)	7.3 (184)	50 (22.5)
ODX-AGM27M	1750	1080	92	195	12.4 (315)	6.8 (172)	8.8 (222)	8.1 (206)	68 (31.0)
ODX-AGM65M	1750	1070	69	135	11.8 (299)	7.3 (186)	7.4 (188)	6.8 (172)	54 (24.5)
ODX-AGM31M	2150	1370	100	220	13.0 (331)	6.8 (173)	9.4 (239)	8.6 (218)	78 (35.5)
ODS-AGM6M	2250	1550	114	240	11.3 (286)	10.6 (269)	9.2 (233)	9.2 (233)	86 (39.0)
ODX-AGM8DK	3125	2700	228	500	21.0 (521)	11 (279)	9.4 (239)	8.0 (206)	187 (85.0)
ODX-AGM8DKDT	3125	2700	228	500	21.0 (521)	11 (279)	9.4 (239)	8.0 (206)	187 (85.0)
ODX-AGM8DKT	3125	2700	228	500	21.0 (521)	11 (279)	9.4 (239)	8.0 (206)	187 (85.0)

Construction Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)

Case Material Polycarbonate Blend*

Terminals Tin-Coated Brass/Solid Brass**

Top Lead Style Over-the-wall***

ODYSSEY® Performance Batteries

12 volt

PART NUMBER	PHCA 5 sec [A]	MCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODP-AGM24M	1300	825	63	155	10.9 (276)	6.8 (172)	8.9 (225)	8.1 (206)	51 (23.0)
ODP-AGM27M	1500	975	85	182	12.4 (316)	5.8 (147)	8.9 (225)	8.1 (206)	60 (27.0)
ODP-AGM34M	1300	810	60	120	10.8 (275)	6.8 (172)	7.9 (201)	7.4 (187)	48 (21.5)
ODP-AGM31M	1750	1050	87	190	13.0 (330)	6.8 (173)	9.5 (240)	8.6 (220)	69 (31.5)
ODP-AGM4D	2400	1549	170	370	20.4 (518)	8.8 (223)	8.6 (218)	8.3 (208)	117 (53.5)
ODP-AGM8D	2700	1787	220	475	20.4 (518)	10.9 (276)	8.9 (225)	8.5 (215)	143 (65.0)

Construction Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)

Case Material Polypropylene

Terminals Solid Lead/Solid Brass**

Top Lead Style Through-the-wall

