

## ODYSSEY® Extreme Batteries

12 volt

PART NUMBER	PHCA 5 sec [A]	CCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODX-AGM31	2150	1150	100	220	13.0 (330)	6.8 (173)	9.5 (241)	8.5 (216)	78 (35.5)

Construction	Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)
Case Material	Polycarbonate Blend*
Terminals	Stainless steel stud with lead base
Top Lead Style	Over-the-wall**



ODX-AGM31

## ODYSSEY® Performance Batteries

12 volt

PART NUMBER	PHCA 5 sec [A]	CCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODP-AGM31	1750	925	100	200	13.0 (330)	6.8 (173)	9.6 (243)	8.6 (219)	70 (31.5)

Construction	Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)
Case Material	Polypropylene
Terminals	Stainless steel stud with lead base
Top Lead Style	Through-the-wall



ODP-AGM31