

Deka Commercial Batteries

GROUP NO.	PART NO.	PERFORMANCE LEVEL			WEIGHT (LB.)	MAXIMUM OVERALL DIMENSIONS						CORE VALUE	FOOTNOTES
		CCA	R.C.	REF. CA		LENGTH		WIDTH		HEIGHT			
						in	mm	in	mm	in	mm		
8-VOLT COMMERCIAL SERVICE													
1	801	520	102	640	32	8-7/8	225	6-3/4	171	8-7/8	225	1.0	12,25
6-VOLT HEAVY-DUTY COMMERCIAL SERVICE													
1	901MF	640	130	785	33	9	229	6-7/8	175	8-3/4	222	1.0	21,25
2	902	675	185	830	37	10-3/8	264	6-7/8	175	8-3/4	222	1.0	12,25
3EH	93EH	875	250	1075	47	19-1/4	489	4-1/4	108	10	254	1.0	12,25
4	904MF	975	250	1200	48	12-1/2	318	6-7/8	175	9-1/2	241	1.5	21,25
5D	905D	880	250	1080	54.5	13-3/8	340	7-1/8	181	9-1/4	235	1.5	12,25
12-VOLT HEAVY-DUTY COMMERCIAL SERVICE													
3ET	3ET	3ET	3ET	3ET	3ET	3ET	489	4-1/4	108	9-7/8	251	1.0	12,25
4D	904D	1050	290	1290	97	20-1/2	520	8-5/8	219	9-7/8	251	3.0	12,17,21,22
4DLT	94DLT	850	240	1045	78.5	20	508	8-1/8	206	8-1/8	206	2.0	12,19,25
8D	908DFT	1425	440	1755	127	20-3/4	527	11	279	10	254	4.0	12,17,21,22
	708D	1100	325	1355	114.5							4.0	12,17,25
17TF	917TF	530	140	650	63	17	432	6-7/8	175	8	203	1.5	11,15,19,25
28	928MF	550	100	675	42.5	10-1/4	260	6-3/4	171	9-1/2	241	1.0	21,22,X
30H	930H	650	150	800	51	13	330	6-3/4	171	9-1/2	241	1.5	19,21,22
31	1231MF	1000	185	1230	60	13	330	6-3/4	171	9-1/2	241	1.5	17,19,21,22,X
	1131MF	950	175	1170	56.5							1.5	17,19,21,22,X
	1031MF	760	170	935	53.5							1.5	17,19,21,22,X
	931MF	650	150	800	52							1.5	17,19,21,22,X
31P	1231PMF	1000	185	1230	60	13	330	6-3/4	171	9-1/2	241	1.5	17,19,21,22
	1131PMF	950	175	1170	56.5							1.5	17,19,21,22
	1031PMF	760	170	935	53.5							1.5	17,19,21,22
	931PMF	650	150	800	52							1.5	17,19,21,22
12-VOLT HEAVY-DUTY COMMERCIAL SEVERE SERVICE/DUAL PURPOSE													
31	7T31	730	190	900	62	13	330	6-3/4	171	9-1/2	241	1.5	17,19,21,22,X
31P	7T31P	730	190	900	62							1.5	17,19,21,22
31	DP31CS	700	185	860	57							1.5	17,19,21,22,X

